



ENCLOSURE AIR CONDITIONERS
High Capacity Series
15,000 BTUH

Celebrating
 20 Years of
 Excellence

Engineered & manufactured to endure the most difficult of environments and applications. ISC air conditioners will exceed environmental requirements in applications like Steel, Food Processing, Petro-Chemical, Cement, Paper & Pulp and Plastics



**Indoor/Outdoor NEMA Type 12, 4 and 4X
 Closed Loop Systems**

Digital Temperature Controller

- ◆ Programmable set point and temperature operating controls
- ◆ Visible error and/or alarm messaging
- ◆ System status indication
- ◆ Password protection

Independent Active Condensate Management System

- ◆ Elimination of condensate
- ◆ Eradicates condensate without corrosive contact with coils

Unit Efficiency

- ◆ Pressure operated blower control reduces power inrush and saves energy
- ◆ Fully insulated & sealed cabinet
- ◆ Temperature Control Valve to provide a broad temperature range while maintaining cooling capacity
- ◆ Washable Filter Media

Industrial Construction

- ◆ Free standing rigid chassis eases maintenance
- ◆ Durable 16 gauge welded steel construction with a hard wearing powder coated finish for NEMA Type 12 and 4; 304 Stainless Steel for NEMA Type 4X
- ◆ Tamper Resistant Hardware

Compressor Protection System

- ◆ High & Low refrigerant cutoffs with fault indication
- ◆ Compressor anti short cycle protection
- ◆ Compressor run capacitors reduce power inrush, save energy and increase compressor life

Options:

- ◆ High Ambient Package
- ◆ Corrosive Environment Protection
- ◆ External Alarm Capabilities
- ◆ Dry Contact Remote Monitoring
- ◆ Integrated Enclosure Heater System
- ◆ Low Ambient Protection
- ◆ NEMA Type 12, 4 and 4X
- ◆ Hazardous Area Models
- ◆ 316 Stainless Steel Construction
- ◆ Remote Programmable Controller

Part Number	NEMA Type	BTUH	Watts	Volts/ Hz.	Running Amps	Max Ambient Temperature	Dimensions H x W x D	Net Weight
ISC-HC-150-236-XX-XXX	12,04,4X	15,000	4395	230/60	8.41	125°F	56 x 23.3 x 15.17	186
ISC-HC-150-486-XX-XXX	12,04,4X	15,000	4395	486/60	4.21	125°F	65.6 x 23.3 x 15.17	225

Information Subject to change without notice