



ENCLOSURE AIR CONDITIONERS

High Capacity Series



10,000 BTUH - 20,000 BTUH MODELS

Designed for Higher Capacity Requirements
Indoor/Outdoor NEMA Type 12, 4 and 4X Closed Loop Systems

Unique Condensate Management System evaporates moisture from the enclosure thus eliminating drain tubes, buckets, and wet floors in typical applications.

Compressor Protection System includes high and low refrigerant cutoffs with fault protection, anti short cycle protection, and compressor run capacitors to increase compressor life and save energy.

Highly Efficient with fully insulated and sealed cabinets, and pressure operated blowers that reduce power inrush and saves energy.

Digital Temperature Controller with programmable set points, visible error and/or alarm messaging and system status indication.

Maintains UL/cUL Type 12, 4 or 4X rating when properly installed on a UL/cUL Type 12, 4 or 4 X rated enclosure.

UL/cUL Listed; File No. SA8067



SPECIFICATIONS

Part Number	BTUH	Watts	Volts /Hz.	Running Amps	Max Ambient Temperature	Dimensions H x W x D	Net Weight
ISC-HC-100-126-XX-XXX	10,000	2930	120/60	16.3	125°F	48"X15.86"x15.03	135
ISC-HC-100-236-XX-XXX	10,000	2930	230/60	8.12	125°F	48"X15.86"x15.03	135
ISC-HC-100-486-XX-XXX	10,000	2930	480/60	4.06	125°F	56.6"X15.86"x15.03	185
ISC-HC-120-126-XX-XXX	12,000	3516	120/60	16.3	125°F	48"X15.86"x15.03	135
ISC-HC-120-236-XX-XXX	12,000	3516	230/60	8.12	125°F	48"X15.86"x15.03	135
ISC-HC-120-486-XX-XXX	12,000	3516	480/60	4.06	125°F	56.6"X15.86"x15.03	185
ISC-HC-150-236-XX-XXX	15,000	4395	230/60	8.41	125°F	56"X23.3"x15.17"	175
ISC-HC-150-486-XX-XXX	15,000	4395	480/60	4.21	125°F	65.6"X23.3"x15.17"	225
ISC-HC-155-236-XX-XXX	15,000	4395	230/60	8.41	125°F	48"X15.86"x15.03	135
ISC-HC-155-486-XX-XXX	15,000	4395	480/60	4.21	125°F	56.6"X15.86"x15.03	185
ISC-HC-200-236-XX-XXX	20,000	5860	230/60	11.27	125°F	56"X23.3"x15.17"	175
ISC-HC-200-486-XX-XXX	20,000	5860	480/60	5.64	125°F	65.6"X23.3"x15.17"	225

Information Subject to change without notice

4421 Tradition Trail • Plano, Texas 75093 • 972-964-2700 or 800-836-7472 • Fax 972-964-2755
Web: www.iscenclosurecooling.com • Email: iscinfo@iscsales.com