



# ENCLOSURE AIR CONDITIONERS

## Narrow Edge Series



### 1000 BTUH - 8000 BTUH MODELS

### Designed to fit 12in. Panels

Indoor/Outdoor NEMA Type 12, 4 and 4X Closed Loop Systems



**Unique Condensate Management System** evaporates moisture from the enclosure thus eliminating drain tubes, buckets, and wet floors in typical applications.

**Compressor Protection System** includes high and low refrigerant cutoffs with fault protection, anti short cycle protection, and compressor run capacitors to increase compressor life and save energy.

**Highly Efficient** with fully insulated and sealed cabinets, and pressure operated blowers that reduce power inrush and saves energy.

**Digital Temperature Controller** with programmable set points, visible error and/or alarm messaging and system status indication.

**Maintains UL/cUL Type 12, 4 or 4X rating** when properly installed on a UL/cUL Type 12, 4 or 4 X rated enclosure.

*UL/cUL Listed; File No. SA8067*

### SPECIFICATIONS

Part Number	BTUH	Watts	Volts /Hz.	Running Amps	Max Ambient Temperature	Dimensions H x W x D	Net Weight
ISC-NE-010-126-XX-XXX	1000	293	120/60	3.44	125°F	22"x11.8"x8.5"	50
ISC-NE-010-236-XX-XXX	1000	293	230/60	2.06	125°F	22"x11.8"x8.5"	50
ISC-NE-015-126-XX-XXX	1500	440	120/60	3.49	125°F	22"x11.8"x8.5"	50
ISC-NE-015-236-XX-XXX	1500	440	230/60	2.06	125°F	22"x11.8"x8.5"	50
ISC-NE-020-126-XX-XXX	2000	586	120/60	3.76	125°F	32"x11.8"x9.5"	60
ISC-NE-020-236-XX-XXX	2000	586	230/60	1.88	125°F	32"x11.8"x9.5"	60
ISC-NE-020-486-XX-XXX	2000	586	480/60	.94	125°F	37.71"x11.8"x9.5"	105
ISC-NE-030-126-XX-XXX	3000	879	120/60	5.15	125°F	32"x11.8"x9.5"	60
ISC-NE-030-236-XX-XXX	3000	879	230/60	3.61	125°F	32"x11.8"x9.5"	60
ISC-NE-030-486-XX-XXX	3000	879	480/60	1.29	125°F	37.71"x11.8"x9.5"	105
ISC-NE-040-126-XX-XXX	4000	1172	120/60	5.53	125°F	32"x11.8"x9.5"	60
ISC-NE-040-236-XX-XXX	4000	1172	230/60	3.26	125°F	32"x11.8"x9.5"	60
ISC-NE-040-486-XX-XXX	4000	1172	480/60	1.38	125°F	37.71"x11.8"x9.5"	105
ISC-NE-050-126-XX-XXX	5000	1465	120/60	7.70	125°F	36"x11.8"x15"	85
ISC-NE-050-236-XX-XXX	5000	1465	230/60	4.07	125°F	36"x11.8"x15"	85
ISC-NE-050-486-XX-XXX	5000	1465	480/60	2.04	125°F	44.63"x11.8"x15"	145
ISC-NE-060-126-XX-XXX	6000	1758	120/60	7.83	125°F	36"x11.8"x15"	85
ISC-NE-060-236-XX-XXX	6000	1758	230/60	4.95	125°F	36"x11.8"x15"	85
ISC-NE-060-486-XX-XXX	6000	1758	480/60	2.48	125°F	44.63"x11.8"x15"	145
ISC-NE-080-126-XX-XXX	8000	2344	120/60	8.70	125°F	36"x11.8"x15"	90
ISC-NE-080-236-XX-XXX	8000	2344	230/60	5.05	125°F	36"x11.8"x15"	90
ISC-NE-080-486-XX-XXX	8000	2344	480/60	2.53	125°F	44.63"x11.8"x15"	150

Information Subject to change without notice