



ENCLOSURE AIR CONDITIONERS

WF Series



6,000 & 8,000 BTUH MODELS

Designed to Fit Enclosures Requiring a Smaller Depth A/C
Indoor/Outdoor NEMA Type 12, 4 and 4X Closed Loop Systems

Unique Condensate Management System evaporates moisture from the enclosure thus eliminating drain tubes, buckets, and wet floors in typical applications.

Compressor Protection System includes high and low refrigerant cutoffs with fault protection, anti short cycle protection, and compressor run capacitors to increase compressor life and save energy.

Highly Efficient with fully insulated and sealed cabinets, and pressure operated blowers that reduce power inrush and saves energy.

Digital Temperature Controller with programmable set points, visible error and/or alarm messaging and system status indication.

Maintains UL/cUL Type 12, 4 or 4X rating when properly installed on a UL/cUL Type 12, 4 or 4 X rated enclosure.
UL/cUL Listed; File No. SA8067



SPECIFICATIONS

Part Number	BTUH	Watts	Volts /Hz.	Running Amps	Max Ambient Temperature	Dimensions H x W x D	Net Weight
ISC-WF-060-126-12-XXX	6000	1758	120/60	13.3	125°F	36.81"x19"x10.5"	90
ISC-WF-060-236-12-XXX	6000	1758	230/60	9.0	125°F	36.81"x19"x10.5"	90
ISC-WF-060-126-04-XXX	6000	1758	120/60	13.3	125°F	36.81"x19"x10.5"	90
ISC-WF-060-236-04-XXX	6000	1758	230/60	9.0	125°F	36.81"x19"x10.5"	90
ISC-WF-060-126-4X-XXX	6000	1758	120/60	13.3	125°F	36.81"x19"x10.5"	90
ISC-WF-060-236-4X-XXX	6000	1758	230/60	9.0	125°F	36.81"x19"x10.5"	90
ISC-WF-080-126-12-XXX	8000	2344	120/60	12.85	125°F	36.81"x19"x10.5"	90
ISC-WF-080-236-12-XXX	8000	2344	230/60	9.0	125°F	36.81"x19"x10.5"	90
ISC-WF-080-126-04-XXX	8000	2344	120/60	12.85	125°F	36.81"x19"x10.5"	90
ISC-WF-080-236-04-XXX	8000	2344	230/60	9.0	125°F	36.81"x19"x10.5"	90
ISC-WF-080-126-4X-XXX	8000	2344	120/60	12.85	125°F	36.81"x19"x10.5"	90
ISC-WF-080-236-4X-XXX	8000	2344	230/60	9.0	125°F	36.81"x19"x10.5"	90

Information Subject to change without notice