



# ENCLOSURE AIR CONDITIONERS

## WF Series



### 6,000 & 8,000 BTUH MODELS

Designed to Fit Enclosures Requiring a Smaller Depth A/C  
Indoor/Outdoor NEMA Type 12, 4 and 4X Closed Loop Systems

**Unique Condensate Management System** evaporates moisture from the enclosure thus eliminating drain tubes, buckets, and wet floors in typical applications.

**Compressor Protection System** includes high and low refrigerant cutoffs with fault protection, anti short cycle protection, and compressor run capacitors to increase compressor life and save energy.

**Highly Efficient** with fully insulated and sealed cabinets, and pressure operated blowers that reduce power inrush and saves energy.

**Digital Temperature Controller** with programmable set points, visible error and/or alarm messaging and system status indication.

**Maintains UL/cUL** Type 12, 4 or 4X rating when properly installed on a UL/cUL Type 12, 4 or 4 X rated enclosure.  
UL/cUL Listed; File No. SA8067



### SPECIFICATIONS

| Part Number           | BTUH | Watts | Volts /Hz. | Running Amps | Max Ambient Temperature | Dimensions H x W x D | Net Weight |
|-----------------------|------|-------|------------|--------------|-------------------------|----------------------|------------|
| ISC-WF-060-126-12-XXX | 6000 | 1758  | 120/60     | 7.83         | 125°F                   | 36.81"x19"x10.5"     | 90         |
| ISC-WF-060-236-12-XXX | 6000 | 1758  | 230/60     | 4.95         | 125°F                   | 36.81"x19"x10.5"     | 90         |
| ISC-WF-060-486-12-XXX | 6000 | 1758  | 480/60     | 2.48         | 125°F                   | 36.81"x19"x10.5"     | 125        |
| ISC-WF-060-126-04-XXX | 6000 | 1758  | 120/60     | 7.83         | 125°F                   | 36.81"x19"x10.5"     | 90         |
| ISC-WF-060-236-04-XXX | 6000 | 1758  | 230/60     | 4.95         | 125°F                   | 36.81"x19"x10.5"     | 90         |
| ISC-WF-060-486-04-XXX | 6000 | 1758  | 480/60     | 2.48         | 125°F                   | 36.81"x19"x10.5"     | 125        |
| ISC-WF-060-126-4X-XXX | 6000 | 1758  | 120/60     | 7.83         | 125°F                   | 36.81"x19"x10.5"     | 90         |
| ISC-WF-060-236-4X-XXX | 6000 | 1758  | 230/60     | 4.95         | 125°F                   | 36.81"x19"x10.5"     | 90         |
| ISC-WF-060-486-4X-XXX | 6000 | 1758  | 480/60     | 2.48         | 125°F                   | 36.81"x19"x10.5"     | 125        |
| ISC-WF-080-126-12-XXX | 8000 | 2344  | 120/60     | 8.7          | 125°F                   | 36.81"x19"x10.5"     | 90         |
| ISC-WF-080-236-12-XXX | 8000 | 2344  | 230/60     | 5.05         | 125°F                   | 36.81"x19"x10.5"     | 90         |
| ISC-WF-080-486-12-XXX | 8000 | 2344  | 480/60     | 2.53         | 125°F                   | 36.81"x19"x10.5"     | 125        |
| ISC-WF-080-126-04-XXX | 8000 | 2344  | 120/60     | 8.7          | 125°F                   | 36.81"x19"x10.5"     | 90         |
| ISC-WF-080-236-04-XXX | 8000 | 2344  | 230/60     | 5.05         | 125°F                   | 36.81"x19"x10.5"     | 90         |
| ISC-WF-080-486-04-XXX | 8000 | 2344  | 480/60     | 2.53         | 125°F                   | 36.81"x19"x10.5"     | 125        |
| ISC-WF-080-126-4X-XXX | 8000 | 2344  | 120/60     | 8.7          | 125°F                   | 36.81"x19"x10.5"     | 90         |
| ISC-WF-080-236-4X-XXX | 8000 | 2344  | 230/60     | 5.05         | 125°F                   | 36.81"x19"x10.5"     | 90         |
| ISC-WF-080-486-4X-XXX | 8000 | 2344  | 480/60     | 2.53         | 125°F                   | 36.81"x19"x10.5"     | 125        |

Information Subject to change without notice

4421 Tradition Trail • Plano, Texas 75093 • 972-964-2700 or 800-836-7472 • Fax 972-964-2755  
Web: [www.iscenclosurecooling.com](http://www.iscenclosurecooling.com) • Email: [iscinfo@iscsales.com](mailto:iscinfo@iscsales.com)